

WE series



Industrial Machinery Sales & Service Pty Ltd

Phone: +61 8 8346 7779

info@industrialmachinery.net.au

www.industrialmachinery.net.au



WE-270 DSA

SEMI-AUTO


● : Standard ◎ : Optional — : Unable to Install

Operation	Manual	Semi-Auto
Model		WE-270 DSA
Inverter Speed Control (DSV/DSAV)		—
Blade Broken Detection		●
Dual Angle Cutting 60° (R) ~ 45° (L)		●
Two Blade Speed Switch		●
Downfeed Hydraulic Control		●
Manual Vise Clamping (DS/DSV)		—
Manual Trigger Switch or Auto-Cutting		—
Hydraulic Vise Clamping (DSA/DSAV)		●
Semi-Auto Type (DSA/DSAV)		●
Blade Tension Indicator		●

SPECIFICATIONS

Capacity (HxW)	90°	○ 220 mm □ 215 mm □ 105 x 260 mm
	45°	○ 150 mm □ 145 mm □ 70 x 155 mm
	60°	○ 90 mm □ 85 mm □ 85 x 90 mm
	L45°	○ 135 mm □ 110 mm □ 45 x 160 mm
Blade Size	27 x 0.9 x 2460 mm	
Blade Speed	2 Speeds	50HZ 4P 72 m/min 8P 36 m/min
	Inverter	20 ~ 85 mpm
Blade Motor	1.5 HP (1.1 kW)	
Hydraulic / Coolant Motor	1 / 2 HP (0.38 kW) / 50W	
Container Loads	10 units / 20' 20 units / 40'	
Packing Size	1550 x 745 x 1055 mm (DS/DSV)	
	1550 x 745 x 1575 mm (DSA/DSAV)	
N.W./G.W.	280 kg / 330 kg	

* The above package sizes are for reference only; actual packing size is based on the actual shipments conditions.



ELECTRONIC OPERATION
CONTROL PANEL
With lights for indicating
or trouble-shooting problems.

WE series



Industrial Machinery Sales & Service Pty Ltd

Phone: +61 8 8346 7779

info@industrialmachinery.net.au

www.industrialmachinery.net.au



WE-350 DSA

SEMI-AUTO


● : Standard ◎ : Optional — : Unable to Install

Operation		Semi-Auto
Model		WE-350 DSA
Inverter Speed Control (DSV/DSAV)		— —
Blade Broken Detection		●
Dual Angle Cutting 60° (R) ~ 45° (L)		●
Two Blade Speed Switch		●
Downfeed Hydraulic Control		●
Manual Vise Clamping (DS/DSV)		— —
Manual Trigger Switch or Auto-Cutting		— —
Hydraulic Vise Clamping (DSA/DSAV)		●
Semi-Auto Type (DSA/DSAV)		●
Blade Tension Indicator		●

SPECIFICATIONS

Capacity (HxW)	90°	○ 260 mm □ 260 mm ▢ 250 x 350 mm
	45°	○ 230 mm □ 165 mm ▢ 110 x 240 mm
	60°	○ 150 mm □ 90 mm ▢ 90 x 150 mm
	L45°	○ 200 mm □ 170 mm ▢ 60 x 260 mm
Blade Size	27 x 0.9 x 3160 mm	
Blade Speed	2 Speeds	50HZ 4P 72 m/min 8P 36 m/min
	Inverter	20 ~ 85 mpm
Blade Motor	2 HP (1.5 kW)	
Hydraulic / Coolant Motor	1 / 2 HP (0.38 kW) / 50W	
Container Loads	18 units / 20' 36 units / 40'	
Packing Size	1735 x 750 x 1120 mm (DS/DSV)	
	1850 x 750 x 1710 mm (DSA/DSAV)	
N.W./G.W.	360 kg / 410 kg	

* The above package sizes are for reference only; actual packing size is based on the actual shipments conditions.



ELECTRONIC OPERATION CONTROL PANEL
With lights for indicating or trouble-shooting problems.